

Fosroc® Nitobond® HAR



constructive solutions

Polymer emulsion bonding agent

Uses

Nitobond HAR is the recommended primer for the Renderoc cementitious repair system.

Advantages

- Single component - no site mixing
- Easy to use - ready to use straight from container
- High bond strength - excellent bond strength between Renderoc systems and concrete
- Non-flammable
- Cost effective - economical in use

Description

Nitobond HAR is a single component polymer emulsion system designed as a bonding agent for Renderoc repair products.

Application Instructions

Preparation

All surfaces should be clean and free from dust and contamination.

Application

The substrate should be thoroughly soaked with clean water and any excess removed prior to applying one coat of Nitobond HAR primer and scrubbing it well into the surface. The Renderoc mortar can be applied as soon as the primer becomes tacky. If the Nitobond HAR is too wet, overhead and vertical build-up of the Renderoc mortar may be difficult.

If the Nitobond HAR primer dries before the application of the Renderoc mortar, the area must be re-primed before proceeding. In exceptional circumstances, e.g. where a substrate/repair barrier is required or where the substrate is wet or likely to remain permanently damp, Nitobond EP bonding aid should be used. Contact Fosroc for further information.

Note: Nitobond HAR primer is generally not used when spraying Renderoc mortars.

Cleaning

Wash all equipment with clean water immediately after use.

Important notice

A Safety Data Sheet (SDS) is available from the Fosroc website. Read the SDS and TDS carefully prior to use as application or performance data may change from time to time. In emergency, contact any Poisons Information Centre (phone 13 11 26 within Australia) or a doctor for advice.

Product disclaimer

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.

Limitations

Do not use Nitobond HAR when the temperature is below 5°C and falling.

Supply

Nitobond HAR 1 litre:	FC322070-1L
Nitobond HAR 5 litre:	FC322070-5L
Nitobond HAR 20 litre:	FC322070-20L

Coverage

Nitobond HAR: 4 - 6 m²/litre

Storage

Nitobond HAR should be stored in dry conditions at 5°C to 25°C in original unopened packaging.

Protect from frost.



constructive solutions

*Manufactured and sold under license from Fosroc International Limited. Fosroc and the Fosroc logo are trade marks of Fosroc International Limited, used under license.

Parchem Construction Supplies Pty Ltd
7 Lucca Road, Wyong NSW 2259

Ph: 1800 812 864

www.fosroc.com.au

ABN 80 069 961 968

Distributed in New Zealand by: Concrete Plus Ltd
150 Hutt Park Road Gracefield Ph: 0800 657 156
www.fosroc.co.nz NZBN 9429033691282

Oct 2017