

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

## **TEST REPORT**

Client : Parchem Construction Supplies Pty Ltd 7 Lucca Road Wyong NSW 2164

Melting

 Test Number
 :
 21-001312

 Issue Date
 :
 3/05/2021

 Print Date
 :
 3/05/2021

Sample Description	Resin applied to cement s Colour : Grey End Use : Floor topping Nominal Composition : Nominal Mass per Unit Ar	g system Novolac Epoxy rea/Density :	1120kg/m3					
AS ISO 9239.1-2003	Nominal Thickness : 0.4mm Reaction to Fire Tests for Floorings. Determination of the Burning Behaviour using a							
A0 100 J203.1-2000	Radiant Heat Source							
	Date of Sample Arrival 17-03-2021							
	Date Tested		03-05-2021					
	CHF Value		1	2	3	Mean		
	Non Directional		8.6	10.7	9.2	9.5	kW/m²	
	Smoke Value		1	2	3	Mean		
	Non Directional		241	83	192	172	%.min	

236016

50451

C Australian Wool Testing Authority Ltd Copyright - All Rights Reserved Accredited for compliance with ISO/IEC 17025 - Testing



Page 1 of 2

Yes

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

12



MICHAEL A. JACKSON B.Sc.(Hons)

0204/11/06



Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

## **TEST REPORT**

Client : Parchem Construction Supplies Pty Ltd 7 Lucca Road Wyong NSW 2164

 Test Number
 :
 21-001312

 Issue Date
 :
 3/05/2021

 Print Date
 :
 3/05/2021

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BSEN 13238:2010 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

No directional properties, three specimens tested only.

Each specimen was clamped as supplied by client prior to testing.

HF30 not reported as flame out time occurred before 30 minutes.

Results in accordance with section 8.4 have not been included in the report. They are available upon request.

236016

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved 50451

ΝΔΤΔ

Accredited for compliance with ISO/IEC 17025 - Testing

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

12



Page 2 of 2





C