
As suppliers of building and civil engineering products Parchem Construction Supplies Pty Ltd do not offer a design service. Information in this drawing is a suggestion only and must not be used for construction except as a signed off drawing by the specifier or contractor



(a) PLAN VIEW
*FOR TIMBER FLOORS - WATERPROOF ENTIRE FLOOR

1500 SEE FIGURE (a) WATERPROOF TO 1800 FROM FINISHED FLOOR LEVEL, WIDTH 40mm EITHER SIDE OF JUNCTION SHOWER PANEL SEALED AT ALL JUNCTIONS 1500 MEASURED FROM THE SHOWER WATER CONNECTION AT THE WALL **SHOWER SCREEN** RESISTANT WATER RESISTANT WALLS TO 1800 FROM FINISHED FLOOR LEVEL SEAL TAP, SHOWER ROSE AND BATH SPOUT PENETRATIONS WATERPROOF BATH/WALL JUNCTION TO MAKE JUNCTION WATERPROOF WATERPROOF JUNCTION WIDTH OF 40mm EITHER SIDE OF THE JUNCTION WATERPROOF JUNCTION TO 1300mm FROM THE SHOWER CONNECTION AT THE WALL AND 25mm ABOVE WATER RESISTANT 150 FINISHED FLOOR LEVEL WATERPROOF JUNCTION WATERPROOF **FLOOR WASTE** WATERPROOF BATH LIP/TILE JOINT WATERPROOF TO 1500 FROM SHOWER CONNECTION AT WALL AND GRADE (b) ISOMETRIC VIEW TO A FLOOR WASTE* NOTE: ALL DIMENSIONS IN mm

EXTENT OF TREATMENT OF WET AREAS - MEETS AS3740 (CONCRETE & COMPRESSED FC SHEET FLOOR)

SCALE:- NTS

DRAWN BY:- MN
DATE:- 16-7-13

LATEST AMENDMENT:- PJ DATE:-23/10/19 TSD/W-WASD04

ISSUE NUMBER 2



PARCHEM CONSTRUCTION SUPPLIES 7 LUCCA ROAD, WYONG NSW 2259

www.fosroc.com.au

1800 812 864

Fosroc and the Fosroc logo, are the trade marks of FosrocInternational Limited, used under licence